

# Information Technology Engineering Support for HRSA Data Systems

## Ryan White Services Report (RSR) Data Dictionary and XML Schema Implementation Guide Release 3.2

Prepared in support of  
Health Resources and Services Administration  
**Contract:** HRSA Bureau Reporting Systems  
**Contract Number:** HSH250201100069B

**November 10, 2014**

Submitted to:



Health Resources and Services Administration  
5600 Fishers Lane  
Rockville, MD 20857

Submitted by:



Leidos Health  
Health Informatics & Infrastructure Solutions  
12530 Parklawn Drive, Suite 350  
Rockville, MD 20852

### DISCLOSURE LEGEND

This document includes data that shall not be disclosed outside the government and shall not be duplicated, used, or disclosed in whole or in part for any purpose other than for which it was intended. The restriction does not limit the Government's right to use information contained in these data if they are obtained from another source without restriction. The data subject to this restriction are contained in sheets marked as restricted.

## Document Version History

Version	Date	Description
1.1	26-FEB-2009	Removed text "Must be within the reporting period start and end dates" from the Allowed Values column for Item 47, FirstOutpatientAmbulatoryCareDate.
1.2	11-MAR-2009	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Changed RiskScreeningProvidedID data type to match XML schema definition and Required Data Elements for Client Data document.</li> <li>Changed SV1 reporting period end date from 12/30/2009 to 12/31/2009</li> <li>Changed 65 2 = Third trimester to 2 = Second trimester</li> </ul>
1.3	02-JUL-2009	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Corrected the number of occurrences for ID2 – vital enrollment status. Changed the value "1-6" to "1".</li> <li>Corrected the number of occurrences for ID5 – ethnicity. Changed the value "1-2" to "1".</li> </ul>
2.0	01-OCT-2009	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Incremented service IDs by 1.</li> <li>Change "Aids" to "Hiv" in screening values.</li> <li>Indicated which fields are required based on which services the client received.</li> <li>Clarified that services that were not delivered do not need to be reported.</li> </ul>
2.1	13-OCT-2009	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Clarified CD4 and viral load formats.</li> <li>Changed Items 58 and 59 required type from "Yes" to "OA".</li> </ul>
2.3	09-JUN-2010	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Added the definition for the XmlVersion element. Non-breaking change.</li> <li>Modified the definition for undetectable viral load counts. Non-breaking change.</li> <li>Deprecated the ReportPeriodID. This value shall no longer be required and will be ignored. Non-breaking change.</li> <li>Added validation text for FirstServiceDate indicating that it should be on or before all other reported service dates.</li> <li>Added validation text for DeathDate indicating that it should be on or after all other reported service dates.</li> <li>Added validation text for BirthYear indicating that it should be on or before all other reported service date years.</li> <li>Added validation text for the GeographicUnitCode indicating that the provider organization's geographic unit code should be used if the client's geographic unit code is not known.</li> <li>Added validation text for the AidsDiagnosisYear indicating that this value must be on or before the last date of the reporting period.</li> <li>Added validation text for the FirstAmbulatoryCareDate indicating that this value must be on or before the last date of the reporting period.</li> <li>Added validation text for ClientReportAmbulatoryService indicating that the ServiceDate values must be within the reporting period start and end dates.</li> <li>Added validation text for ClientReportCd4Test indicating that the ServiceDate values must be within the reporting period start and end dates.</li> </ul>

Version	Date	Description
2.4	22-JUN-2010	Updated restricted geographic unit codes for low-density population areas based on the 2010 U.S. Census.
2.5	20-SEP-2012	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Updated definition for ScreenedTBSinceHivDiagnosisID to be required when ScreenedTBID is also reported as “unknown.”</li> <li>Updated definition for ScreenedHepatitisBSinceHivDiagnosisID to be required when ScreenedHepatitisBID is also reported as “unknown.”</li> <li>Updated definition for ScreenedHepatitisCSinceHivDiagnosisID to be required when ScreenedHepatitisCID is also reported as “unknown.”</li> </ul>
2.5	02-OCT-2012	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Changed TechnicalContactName to TechnicalContactEmail for data element XV5.</li> <li>Changed required value from “All” to “No” for data element SV1.</li> <li>Removed instructions for reporting default values for first service date. The first service date should not be reported if it is not known.</li> <li>Removed instructions for reporting default values for death date. The death date should not be reported if it is not known.</li> <li>Change “2 = Referred to another program or services, or self sufficient” to “2 = Referred to another program or services, or discharged because self-sufficient” in EnrollmentStatusID.</li> </ul>
3.0	01-APR-2014	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>ReportYear and AppendMode nodes were deleted from the Root element.</li> <li>ClientReportMedicalInsurance, ClientReportRace, ClientReportHivRiskFactor, ClientReportServiceVisits, ClientReportServiceDelivered, ClientReportAmbulatoryService, ClientReportCd4Test, and ClientReportViralLoadTest were made children of the ClientReport element.</li> <li>ReportPeriodID, FirstServiceDate, DeathDate, GeographicUnitCode, AidsDiagnosisYear, ScreenedTBID, ScreenedHepatitisBID, ScreenedHepatitisCID, PrenatalCareID, PrescribedArvMedicationID, QuarterID inside ClientReportServiceVisit, and QuarterID inside ClientReportServiceDelivered elements were deleted.</li> <li>ClientReportHispanicSubgroup, ClientReportAsianSubgroup, ClientReportNhpiSubgroup, SexAtBirthID, HivDiagnosisYear, HivPosTestDate, and OamcLinkDate elements were added.</li> <li>Changes were made to the following elements: EnrollmentStatusID, EthnicityID, PovertyLevelID, HousingStatusID, HivAidsStatusID, ClientReportHivRiskFactor, MedicalInsuranceID, ClientReportServiceVisit, ClientReportServiceDelivered, RiskScreeningProvidedID, ClientReportCD4Test, ClientReportViralLoadTest, PrescribedPcpProphylaxisID, PrescribedHaartID, ScreenedTBSinceHivDiagnosisID, ScreenedHepatitisBSinceDiagnosis, VaccinatedHepatitisBID, ScreenedHepatitisCSinceHivDiagnosisID, ScreenedSubstanceAbuseID, ScreenedMentalHealthID, ReceivedCervicalPapSmearID, and PregnantID.</li> </ul>
3.1	15-JUL-2014	The following updates were addressed in this version: <ul style="list-style-type: none"> <li>Revised PovertyLevelID data element: <ul style="list-style-type: none"> <li>Deleted value 1, Equal to or below 100% of the Federal poverty level.</li> <li>Added value 13, Below 100% of the Federal poverty level</li> </ul> </li> </ul>

Version	Date	Description
		<ul style="list-style-type: none"> <li>Revised the HivRiskFactorID data element: <ul style="list-style-type: none"> <li>Deleted value 8, Unknown</li> <li>Added value 9, Risk factor not reported or not identified.</li> </ul> </li> <li>Revised MedicalInsuranceID data element: <ul style="list-style-type: none"> <li>Deleted value 5, No Insurance</li> <li>Deleted value 6, Other</li> <li>Added value 15, Other plan</li> <li>Added value 16, No insurance/uninsured</li> </ul> </li> <li>Revised the HivStatusID data element: <ul style="list-style-type: none"> <li>Deleted value 5, HIV indeterminate (infants only)</li> <li>Added value 7, HIV indeterminate (infants less than 2 years only)</li> </ul> </li> <li>The data element "PrescribedHaartID" has been renamed "PrescribedArtID".</li> <li>Deleted value 6, Unknown, for the ClientReportRace data element.</li> <li>Replaced the word "Deprecated" with the word "Removed" throughout the document for clarity.</li> <li>Clarified the Required field for the data elements HivPosTestDate and OamcLinkDate.</li> <li>Expanded the description of empty or "null" data element tags to include &lt;tag /&gt;.</li> <li>Added "No" and "Yes" to the list of possible values displayed in the Required field of each data element table.</li> <li>Updated the Required field of each data element table in the XML Schema Version Elements and Provider Information Elements sections.</li> <li>Added Reference ID numbers to the data element tables for the following data elements: ClientReportHispanicSubgroup; ClientReportAsianSubgroup, ClientReportNhpiSubgroup, SexAtBirthID, HIVDiagnosisYear, HivPosTestDate, and OamcLinkDate.</li> <li>Reordered the document to group new data elements with similar existing data elements, for example ClientReportHispanicSubgroup is now listed immediately following EthnicityID.</li> <li>Revised the occurrence field throughout the document for greater accuracy. For example, the data element PregnantID is only reported for HIV-positive women who receive an outpatient/ambulatory medical care service. The value in the occurrence field for this data element was changed from "1 per client" to "1 per required client." Other data elements that were changed include ClientReportHispanicSubgroup, ClientReportNhpiSubgroup, ClientReportServiceDelivered, ClientReportAmbulatoryService, and ClientReportCd4Test.</li> <li>Updated the schema sample displayed in the table for data element HivAidsStatus for accuracy.</li> <li>Added a note to the Required field for the data elements ScreenedTBSinceHivDiagnosisID, ScreenedHepatitisBSinceHivDiagnosisID, and ScreenedHepatitisCSinceHivDiagnosisID. These data elements are now required for all clients for whom Clinical Information is reported.</li> <li>Changed the value of the DeliveredID tag for the data element ClientReportServiceDelivered shown in the Sample Client-Level Data XML Format section for accuracy.</li> </ul>

Version	Date	Description
		<ul style="list-style-type: none"> <li>Updated the link to the RSR Schema Definition files.</li> </ul>
3.2	1-NOV-2014	<p>The following updates were addressed in this version:</p> <ul style="list-style-type: none"> <li>Updated schema version number to 4 0 0.</li> <li>Fixed typographical errors in the schema sample displayed in the table for data element ClientReportHivRiskFactor.</li> <li>Fixed typographical and formatting errors in the description for data element HivAidsStatusID.</li> <li>Fixed typographical errors in the schema sample displayed in the table for data element ClientReportMedicalInsurance.</li> <li>Fixed typographical errors in the schema sample displayed in the table for data element ClientReportServiceDelivered.</li> <li>Fixed typographical errors in the schema sample displayed in the table for data element HIVDiagnosisYear.</li> <li>Revised the occurrences field throughout the document to clarify the data elements that may be "NULL".</li> </ul>

## Table of Contents

1	Introduction .....	1
1.1	Purpose .....	1
1.2	Audience .....	1
1.3	Updates .....	2
2	Main Components of the Client-Level XML File .....	2
2.1	File Header .....	2
2.2	Root Element .....	2
2.3	Body: Simple and Complex Elements .....	3
3	RSR Client-Level Data XML Data Elements .....	3
3.1	XML Schema Version Elements .....	4
3.1.1	SchemaVersion .....	4
3.1.2	Originator .....	4
3.1.3	VersionNumber .....	4
3.1.4	TechnicalContactName .....	5
3.1.5	TechnicalContactEmail .....	5
3.1.6	TechnicalContactPhone .....	5
3.1.7	ReportPeriodID (Removed) .....	5
3.1.8	ReportYear (New) .....	6
3.2	Provider Information Elements .....	6
3.2.1	ProviderID .....	6
3.2.2	RegistrationCode .....	6
3.3	Encrypted Unique Client Identifier .....	7
3.3.1	ClientUci .....	7
3.4	Client Demographics .....	7
3.4.1	FirstServiceDate (Removed) .....	7
3.4.2	EnrollmentStatusID (Revised) .....	7
3.4.3	DeathDate (Removed) .....	8
3.4.4	BirthYear .....	8
3.4.5	EthnicityID (Revised) .....	8
3.4.6	ClientReportHispanicSubgroup (New) .....	9
3.4.7	ClientReportRace .....	9
3.4.8	ClientReportAsianSubgroup (New) .....	10
3.4.9	ClientReportNhpiSubgroup (New) .....	10
3.4.10	SexAtBirthID (New) .....	11
3.4.11	GenderID .....	11
3.4.12	TransgenderID .....	11
3.4.13	PovertyLevelID (Revised) .....	11
3.4.14	HousingStatusID (Revised) .....	12
3.4.15	GeographicUnitCode (Removed) .....	12
3.4.16	HivAidsStatusID (Revised) .....	12
3.4.17	AidsDiagnosisYear (Removed) .....	13

3.4.18	ClientReportHivRiskFactor (Revised).....	13
3.4.19	ClientReportMedicalInsurance (Revised).....	14
3.4.20	HIVDiagnosisYear (New) .....	14
3.5	Core Medical Service Visits Delivered (Revised).....	15
3.6	Core Medical and Support Services Delivered (Revised).....	16
3.7	Clinical Information .....	18
3.7.1	RiskScreeningProvidedID (Revised) .....	18
3.7.2	FirstAmbulatoryCareDate.....	18
3.7.3	ClientReportAmbulatoryService .....	18
3.7.4	ClientReportCd4Test (Revised) .....	19
3.7.5	ClientReportViralLoadTest (Revised).....	19
3.7.6	PrescribedPcpProphylaxisID (Revised) .....	20
3.7.7	PrescribedArtID (Revised) .....	21
3.7.8	ScreenedTBID (Removed).....	21
3.7.9	ScreenedTBSinceHivDiagnosisID (Revised) .....	21
3.7.10	ScreenedSyphilisID (Revised).....	22
3.7.11	ScreenedHepatitisBID (Removed) .....	22
3.7.12	ScreenedHepatitisBSinceHivDiagnosisID (Revised).....	22
3.7.13	VaccinatedHepatitisBID (Revised) .....	22
3.7.14	ScreenedHepatitisCID (Removed) .....	23
3.7.15	ScreenedHepatitisCSinceHivDiagnosisID (Revised).....	23
3.7.16	ScreenedSubstanceAbuseID (Revised).....	23
3.7.17	ScreenedMentalHealthID (Revised).....	24
3.7.18	ReceivedCervicalPapSmearID (Revised) .....	24
3.7.19	PregnantID (Revised).....	24
3.7.20	PrenatalCareID (Removed).....	25
3.7.21	PrescribedArvMedicationID (Removed) .....	25
3.8	HIV Counseling and Testing Elements .....	25
3.8.1	HivPosTestDate (New).....	25
3.8.2	OamcLinkDate (New).....	25
4	RSR Client-level Data XML File Format.....	26
4.1	RSR Web Application Validation Checks .....	26
4.2	Sample Client-Level Data XML Format .....	27
Appendix A: List of Acronyms .....		30
Appendix B: Resources.....		31

# 1 Introduction

As a condition of their grant awards, Ryan White HIV/AIDS Program grantees are required to submit the Ryan White HIV/AIDS Program Service Report (RSR) to the Health Resources Services Administration (HRSA) HIV/AIDS Bureau (HAB) annually. The RSR is a client-level data report that provides data on the characteristics of Ryan White HIV/AIDS Program grantees, their providers, and the clients served with program funds.

To submit the RSR successfully, each provider agency that a grantee funds must complete the online section of the provider report and create and upload one or more Extensible Markup Language (XML) files containing client-level data to the RSR Web application. The structure, sequence, values, and format of the data elements in the XML files must conform to the definitions specified in this document. Once the client-level data XML file is uploaded, it is validated for conformance to the data schema and business rules outlined in this document.

**NOTE:** This document does not contain instructions on how to upload the RSR client-level data XML files to the RSR Web application. For instructions on the upload process, please see the RSR Instruction Manual available on the [TARGET website](#).

## 1.1 Purpose

The purpose of this document is to provide reference information on the allowable structure, sequence, values, and format of the RSR client-level data XML files to grantees, providers, and software vendors. This document includes data definitions that describe the meaning of each element in the RSR client-level XML files. In addition, this document describes the required format of the XML file, provides examples of XML files, and includes references to the XML schema definitions that are used to validate the XML file. Ultimately, the goal of this document is to help grantees reduce any errors that may result when they generate and submit client-level data XML files to the RSR Web application.

## 1.2 Audience

This document is intended for RSR technical and/or administrative staff that must collect and report RSR client-level data elements in an XML file format to the HRSA's HAB. Such staff may include developers, data quality specialists, RSR Administrators, or other individuals who are responsible for generating and submitting the RSR.



## 1.3 Updates

This document will be revised as variables and value options are updated or when other global changes are made. The most up-to-date version of this document will be made available on [HRSA's HAB](#) and [TARGET Center](#) websites.

## 2 Main Components of the Client-Level XML File

The RSR client-level data XML file consists of three components: 1) the file header, 2) the root element, and 3) the body elements, which consist of complex and simple data elements.

### 2.1 File Header

The file header is the first line of text in the XML file. It is static text and does not change, and it contains the XML declaration—the version of XML—and encoding being used. A sample file header is shown below:

```
<?xml version="1.0" encoding="UTF-8"?>
```

### 2.2 Root Element

The root element consists of static text and does not change. A root element is required for every XML file, and it serves as “the parent” of all the other elements. In the case of the RSR client-level data XML file, the root element is <RSR:ROOT>, and it appears as follows:

```
<RSR:ROOT xsi:schemaLocation="urn:rsrNamespace  
https://performance.hrsa.gov/hab/rsrExternal/App/XMLSchema/RsrClientSchema.xsd"  
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:RSR="urn:rsrNamespace">
```

The <RSR:ROOT> element contains extra information—called “attributes”—about the file. Each of the attributes has a name and value. The meanings of the attribute names are shown in Table 1.

**Table 1: Root Element Attributes**

Attribute Name	Definition
xsi:schemaLocation	The location of the XML schema definition file used to validate the client-level XML file.
xmlns:xsi	The location of the XML schema instance used to determine the base XML schema standards.
xmlns:CLD	The XML schema namespace used for custom definitions within the XML file.

## 2.3 Body: Simple and Complex Elements

The body of the RSR client-level data XML file contains all the elements under the root element. It contains simple and complex elements. Complex elements contain child elements. Simple elements do not contain any child elements. In the RSR client-level data XML file, the complex data elements must appear in a specific order and contain child data elements to pass the validation check.

Likewise, the simple data elements must appear in a specific order, and the data they contain must conform to the specific rules defined in this data definition document to pass the validation check.

For more information about the other validation checks that the file must pass, please see Section 4: RSR Client-Level Data (CLD) XML File Format.

## 3 RSR Client-Level Data XML Data Elements

This section includes definitions for all the data elements (both complex and simple) in the body of the RSR client-level data XML file. The definitions are presented in tables, and each table includes one or more of the following metadata:

**Reference ID:** This field has been added for convenient referencing between this document and the RSR Instruction Manual. Each element described in this document and in the RSR Instruction Manual shows the unique item number that is assigned to the element in the RSR Instruction Manual.

**Element Name:** The descriptive name of the variable used to provide more information about what is being collected. This corresponds to the label for the variable in the RSR Client-Level Data XML Schema Definitions.

**Definition:** A brief description of the variable.

**Allowed Values:** The type or list of values allowed for the data element.

**Required:** Required data elements are determined based on the type of service the client received. The required values and their meanings are:

- **All** – The element is required for all clients
- **CM** – The element is required for clients receiving medical or non-medical case management services
- **HI** – The element is required for clients receiving: oral health care; early intervention services (A and B); home health care; home and community-based health services; hospice services; mental health services; medical nutrition therapy; substance abuse

services – outpatient; AIDS pharmaceutical assistance (local); or Health Insurance Program (HIP).

- **OA** – The element is required for clients receiving outpatient/medical ambulatory care services.
- **No** – The element is not required to submit the client-level data XML file.
- **Yes** – The element is required and must be included in the client-level data XML file

**Occurrence:** The minimum and maximum number of times the element may appear in a single record within the client-level data XML file.

**Schema:** Sample XML code that indicates the use of the element within the context of the client-level data XML file.

**Comments:** Additional information about the data element.

### 3.1 XML Schema Version Elements

The XML Schema Version elements are designed to capture data about which version of the RSR XML schema is being used.

#### 3.1.1 *SchemaVersion*

Field	Description
ID	XV1
Element Name	SchemaVersion
Parent Element	XmlVersion
Definition	The RSR XML schema version currently supported.
Required	Yes
Occurrence	1 per file
Allowed Values	Must be set to 4 0 0
Schema	<SchemaVersion>4 0 0</SchemaVersion>

#### 3.1.2 *Originator*

Field	Description
ID	XV2
Element Name	Originator
Parent Element	XmlVersion
Definition	The name of the application that generates the client-level data XML file.
Required	Yes
Occurrence	1 per file
Allowed Values	Text from 1 to 150 characters excluding special characters.
Schema	<Originator>Application name</Originator>

#### 3.1.3 *VersionNumber*

Field	Description
ID	XV3
Element Name	VersionNumber
Parent Element	XmlVersion

Field	Description
Definition	The version number of the application that generates the client-level data XML file.
Required	Yes
Occurrence	1 per file
Allowed Values	Text from 1 to 150 characters excluding special characters.
Schema	<VersionNumber>Application version</VersionNumber>

### 3.1.4 *TechnicalContactName*

Field	Description
ID	XV4
Element Name	TechnicalContactName
Parent Element	XmlVersion
Definition	The technical contact name for the application that generates the client-level data XML file.
Required	Yes
Occurrence	1 per file
Allowed Values	Text from 1 to 150 characters excluding special characters.
Schema	<TechnicalContactName>Contact name </TechnicalContactName>

### 3.1.5 *TechnicalContactEmail*

Field	Description
ID	XV5
Element Name	TechnicalContactEmail
Parent Element	XmlVersion
Definition	The technical contact's email address for the application that generates the client-level data XML file.
Required	Yes
Occurrence	1 per file
Allowed Values	The value must be a valid email address.
Schema	<TechnicalContactEmail>Contact email</TechnicalContactEmail>

### 3.1.6 *TechnicalContactPhone*

Field	Description
ID	XV6
Element Name	TechnicalContactPhone
Parent Element	XmlVersion
Definition	The technical contact's phone number for the application that generates the client-level data XML file.
Required	Yes
Occurrence	1 per file
Allowed Values	The format is 999,999,9999 x99999, where the extension ( x99999) is optional, but there must be a space before the "x".
Schema	<TechnicalContactPhone>Contact phone number</TechnicalContactPhone>

### 3.1.7 *ReportPeriodID (Removed)*

Field	Description
ID	SV1
Element Name	ReportPeriodID

Field	Description
Comments	This data element has been removed and should not be included in the client-level data XML file. Instead, please use the ReportYear data element.

### 3.1.8 ReportYear (New)

Field	Description
ID	SV5
Element Name	ReportYear
Parent Element	XmlVersion
Definition	The reporting period identifier.
Required	Yes
Occurrence	1 per file
Allowed Values	yyyy  Must be equal to the reporting period for the submission.
Schema	<ReportYear>yyyy</ReportYear>

## 3.2 Provider Information Elements

### 3.2.1 ProviderID

Field	Description
ID	SV2
Element Name	ProviderID
Parent Element	ClientReport
Definition	The unique provider organization identifier assigned through the Ryan White HIV/AIDS Program Data Report (RDR) or RSR Web application.
Required	No unless it is a batch submittal
Occurrence	0-1 per file
Allowed Values	A system-assigned numeric value.  This variable is not required when uploading the client-level data XML file through the RSR Web application since the file is uploaded into the Provider Report and the provider organization identifier is already known.  However, this value can be provided in the client-level data XML file and will be cross-referenced with the provider organization identifier associated with the Provider Report. If the values do not match, then the client-level data XML file upload will be rejected.
Schema	<ProviderID>Integer</ProviderID>

### 3.2.2 RegistrationCode

Field	Description
ID	SV3
Element Name	RegistrationCode
Parent Element	ClientReport
Definition	The unique provider registration code.
Required	No
Occurrence	0-1 per file

Field	Description
Allowed Values	<p>A system-assigned numeric value.</p> <p>This variable is not required when uploading the client-level data XML file through the RSR Web Application since the file is uploaded into the Provider Report and registration code is already known.</p> <p>However, this value can be provided in the XML file and will be cross-referenced with registration code associated with the Provider Report. If the values do not match, then the XML file upload will be rejected.</p>
Schema	<RegistrationCode>Numeric string</ RegistrationCode >

### 3.3 Encrypted Unique Client Identifier

#### 3.3.1 ClientUci

Field	Description
ID	SV4
Element Name	ClientUci
Parent Element	ClientReport
Definition	The encrypted, unique client identifier generated by the HAB Unique Client Identifier (UCI) generation utilities.
Required	All
Occurrence	1 per client
Allowed Values	40-character upper-case, hexadecimal string plus a single character in the range A-Z.
Schema	<ClientUci>(0-9 A-F)*40 + (A-Z)*1, length 41</ClientUci >

### 3.4 Client Demographics

#### 3.4.1 FirstServiceDate (Removed)

Field	Description
Reference ID	1
Element Name	FirstServiceDate
Comments	This data element has been removed and should not be included in the client-level data XML file.

#### 3.4.2 EnrollmentStatusID (Revised)

Field	Description
Reference ID	2
Element Name	EnrollmentStatusID
Parent Element	ClientReport
Definition	The client's vital enrollment status at the end of the reporting period.
Required	CM, OA
Occurrence	0-1 per required client

Field	Description
Allowed Values	<p>EnrollmentStatusID:</p> <p>1 = Active, continuing in program</p> <p>2 = Referred to another program or services, or self-sufficient</p> <p>3 = Removed from treatment due to violation of rules</p> <p>4 = Incarcerated</p> <p>5 = Relocated</p> <p>6 = Deceased</p> <p>The allowed value below has been removed:</p> <p>7 = Unknown <i>(Removed)</i></p>
Schema	<EnrollmentStatusID>1-6</EnrollmentStatusID>

### 3.4.3 *DeathDate (Removed)*

Field	Description
Reference ID	3
Element Name	DeathDate
Comments	This data element has been removed and should not be included in the client-level data XML file.

### 3.4.4 *BirthYear*

Field	Description
Reference ID	4
Element Name	BirthYear
Parent Element	ClientReport
Definition	<p>Client's year of birth.</p> <p>This value should be on or before all service date years for the client.</p>
Required	All
Occurrence	0-1 per client
Allowed Values	<p>yyyy</p> <p>Must be less than the end of the reporting period.</p>
Schema	<BirthYear>yyyy</BirthYear>

### 3.4.5 *EthnicityID (Revised)*

Field	Description
Reference ID	5
Element Name	EthnicityID
Parent Element	ClientReport
Definition	Client's ethnicity.
Required	All
Occurrence	0-1 per client
Allowed Values	<p>1 = Hispanic/Latino</p> <p>2 = Non-Hispanic/Latino</p> <p>The allowed value below has been removed:</p> <p>3 = Unknown <i>(Removed)</i></p>
Schema	<EthnicityID>1-2</EthnicityID>

### 3.4.6 *ClientReportHispanicSubgroup* (New)

Field	Description
Reference ID	68
Element Name	ClientReportHispanicSubgroup SubgroupID
Parent Element	ClientReport
Definition	Client's Hispanic Subgroup. Report all that apply.
Required	All clients whose ethnicity is "Hispanic" (EthnicityID = 1)
Occurrence	0-4 per required client
Allowed Values	SubgroupID: 1= Mexican, Mexican American, Chicano/a 2= Puerto Rican 3= Cuban 4= Another Hispanic, Latino/a or Spanish origin
Schema	Within the following schema section, multiple SubgroupIDs may be reported. Where multiple SubgroupIDs are reported, multiple sets of corresponding tags should appear (one for each ID)  <pre> &lt;ClientReportHispanicSubgroup&gt;   &lt;SubgroupID&gt;1-4&lt;/SubgroupID&gt;   ...   &lt;SubgroupID&gt;1-4&lt;/SubgroupID&gt; &lt;/ClientReportHispanicSubgroup&gt; </pre>

### 3.4.7 *ClientReportRace*

Field	Description
Reference ID	6
Element Name	ClientReportRace RaceID
Parent Element	ClientReport
Definition	Client's race.
Required	All
Occurrence	0-5 per client
Allowed Values	RaceID: 1 = White 2 = Black or African American 3 = Asian 4 = Native Hawaiian/Pacific Islander 5 = American Indian or Alaska Native  The allowed value below has been removed: 6 = Unknown ( <i>Removed</i> )
Schema	Within the following schema section, multiple RaceIDs may be reported.  <pre> &lt;ClientReportRace&gt;   &lt;RaceID&gt;1-6&lt;/RaceID&gt;   ...   &lt;RaceID&gt;1-6&lt;/RaceID&gt; &lt;/ClientReportRace&gt; </pre>



### 3.4.8 *ClientReportAsianSubgroup (New)*

Field	Description
Reference ID	69
Element Name	ClientReportAsianSubgroup SubgroupID
Parent Element	ClientReport
Definition	Client's Asian subgroup. Report all that apply.
Required	All clients whose race is "Asian" (RaceID = 3)
Occurrence	0-7 per required client
Allowed Values	SubgroupID: 1 = Asian Indian 2 = Chinese 3 = Filipino 4 = Japanese 5 = Korean 6 = Vietnamese 7 = Other Asian
Schema	Within the following schema section, multiple SubgroupIDs may be reported. Where multiple SubgroupIDs are reported, multiple sets of corresponding tags should appear (one for each ID)  <pre> &lt;ClientReportAsianSubgroup&gt;   &lt;SubgroupID&gt;1-7&lt;/SubgroupID&gt;   ...   &lt;SubgroupID&gt;1-7&lt;/SubgroupID&gt; &lt;/ClientReportAsianSubgroup&gt; </pre>

### 3.4.9 *ClientReportNhpiSubgroup (New)*

Field	Description
Reference ID	70
Element Name	ClientReportNhpiSubgroup SubgroupID
Parent Element	ClientReport
Definition	Client's Native Hawaiian/Pacific Islander subgroup. Report all that apply.
Required	All clients whose race is "Native Hawaiian/Pacific Islander" (RaceID = 4)
Occurrence	0-4 per required client
Allowed Values	SubgroupID: 1 = Native Hawaiian 2 = Guamanian or Chamorro 3 = Samoan 4 = Other Pacific Islander
Schema	Within the following schema section, multiple SubgroupIDs may be reported. Where multiple SubgroupIDs are reported, multiple sets of corresponding tags should appear (one for each ID)  <pre> &lt;ClientReportNhpiSubgroup&gt;   &lt;SubgroupID&gt;1-4&lt;/SubgroupID&gt;   ...   &lt;SubgroupID&gt;1-4&lt;/SubgroupID&gt; &lt;/ClientReportNhpiSubgroup&gt; </pre>

### 3.4.10 *SexAtBirthID (New)*

Field	Description
Reference ID	71
Element Name	SexAtBirthID
Parent Element	ClientReport
Definition	The biological sex assigned to the client at birth
Required	All
Occurrence	0-1 per client
Allowed Values	1 = Male 2 = Female
Schema	<SexAtBirthID>1-2</SexAtBirthID>

### 3.4.11 *GenderID*

Field	Description
Reference ID	7
Element Name	GenderID
Parent Element	ClientReport
Definition	Client's current gender.  This is the variable that is used for the encrypted unique client identifier (eUCI).
Required	All
Occurrence	1 per client
Allowed Values	GenderID: 1 = Male 2 = Female 3 = Transgender 4 = Unknown
Schema	<GenderID>1-4</GenderID>

### 3.4.12 *TransgenderID*

Field	Description
Reference ID	8
Element Name	TransgenderID
Parent Element	ClientReport
Definition	Client's current transgender status.
Required	All, if GenderID is "Transgender" (GenderID = 3)
Occurrence	0-1 per required client
Allowed Values	1 = Male to Female 2 = Female to Male 3 = Unknown
Schema	<TransgenderID>1-3</TransgenderID>

### 3.4.13 *PovertyLevelID (Revised)*

Field	Description
Reference ID	9
Element Name	PovertyLevelID
Parent Element	ClientReport
Definition	Client's percent of the Federal poverty level at the end of the reporting period.
Required	CM, OA

Field	Description
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	<p>13 = Below 100% of the Federal poverty level (<i>New</i>)            9 = 100 -138% of the Federal poverty level (<i>New</i>)            10 = 139 - 200% of the Federal poverty level (<i>New</i>)            11 = 201 – 250% of the Federal poverty level (<i>New</i>)            12 = 251 – 400% of the Federal poverty level (<i>New</i>)            7= 401 – 500% of the Federal poverty level (<i>New</i>)            8 = More than 500% of the Federal poverty level (<i>New</i>)</p> <p>The allowed values below have been removed:            1 = Equal to or below 100% of the Federal poverty level (<i>Removed</i>)            2 = 101-200% of the Federal poverty level (<i>Removed</i>)            3 = 201-300% of the Federal poverty level (<i>Removed</i>)            4 = More than 300% of the Federal poverty level (<i>Removed</i>)            5 = Unknown (<i>Removed</i>)</p> <p>The values below are not used for the RSR:            6 = 301-400% of the Federal poverty level (<i>Value not used for RSR</i>)</p>
<b>Schema</b>	<PovertyLevelID>7-13</PovertyLevelID>

### 3.4.14 *HousingStatusID (Revised)*

Field	Description
<b>Reference ID</b>	10
<b>Element Name</b>	HousingStatusID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Client's housing status at the end of the reporting period.
<b>Required</b>	CM, OA, or Housing services
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	<p>1 = Stable/permanent            2 = Temporary            3 = Unstable</p> <p>The allowed value below has been removed:            4 = Unknown (<i>Removed</i>)</p>
<b>Schema</b>	<HousingStatusID>1-3</HousingStatusID>

### 3.4.15 *GeographicUnitCode (Removed)*

Field	Description
<b>Reference ID</b>	11
<b>Element Name</b>	GeographicUnitCode
<b>Comments</b>	This data element has been removed and should not be included in the client-level data XML file.

### 3.4.16 *HivAidsStatusID (Revised)*

Field	Description
<b>Reference ID</b>	12
<b>Element Name</b>	HivAidsStatusID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Client's HIV/AIDS status at the end of the reporting period. Leave this data element blank for HIV affected clients if the client's HIV/AIDS status is not known.

Field	Description
<b>Required</b>	CM, OA
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	<p>HivAidsStatusID:</p> <p>1 = HIV negative</p> <p>2 = HIV-positive, not AIDS</p> <p>3 = HIV-positive, AIDS status unknown</p> <p>4 = CDC-defined AIDS</p> <p>7 = HIV indeterminate (infants less than 2 years only) <i>(New)</i></p> <p>The allowed values below have been removed:</p> <p>5 = HIV indeterminate (infants only) <i>(Removed)</i></p> <p>6 = Unknown <i>(Removed)</i></p>
<b>Schema</b>	<HivAidsStatusID>1-4, 7</HivAidsStatusID>

### 3.4.17 *AidsDiagnosisYear* *(Removed)*

Field	Description
<b>Reference ID</b>	13
<b>Element Name</b>	AidsDiagnosisYear
<b>Comments</b>	This data element has been removed and should not be included in the client-level data XML file.

### 3.4.18 *ClientReportHivRiskFactor* *(Revised)*

Field	Description
<b>Reference ID</b>	14
<b>Element Name</b>	ClientReportHivRiskFactor HivRiskFactorID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	<p>Client's HIV/AIDS risk factor. Report <b>all</b> that apply.</p> <p>For HIV affected clients for whom HIV/AIDS status is not known, leave this value blank.</p>
<b>Required</b>	CM, OA
<b>Occurrence</b>	0-7 per client
<b>Allowed Values</b>	<p>HivRiskFactorID:</p> <p>1 = Male who has sex with male(s) (MSM)</p> <p>2 = Injecting drug use (IDU)</p> <p>3 = Hemophilia/coagulation disorder</p> <p>4 = Heterosexual contact</p> <p>5 = Receipt of blood transfusion, blood components, or tissue</p> <p>6 = Mother w/at risk for HIV infection (perinatal transmission)</p> <p>9 = Risk factor not reported or not identified</p> <p>The allowed values below have been removed:</p> <p>7 = Other <i>(Removed)</i></p> <p>8 = Unknown <i>(Removed)</i></p>

Field	Description
<b>Schema</b>	<p>Within the following schema section, multiple HivRiskFactorIDs may be reported.</p> <pre> &lt;ClientReportHivRiskFactor&gt;   &lt;HivRiskFactorID&gt;1-6, 9&lt;/HivRiskFactorID&gt;   ...   &lt;HivRiskFactorID&gt;1-6, 9&lt;/HivRiskFactorID&gt; &lt;/ClientReportHivRiskFactor&gt; </pre>

### 3.4.19 *ClientReportMedicalInsurance (Revised)*

Field	Description
<b>Reference ID</b>	15
<b>Element Name</b>	ClientReportMedicalInsurance MedicalInsuranceID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Client's medical insurance. Report all that apply.
<b>Required</b>	OA, CM, HI
<b>Occurrence</b>	0-8 per required client
<b>Allowed Values</b>	<p>10 = Private – Employer (<i>New</i>)  11 = Private – Individual (<i>New</i>)  2 = Medicare  12 = Medicaid, CHIP or other public plan (<i>New</i>)  13 = VA, Tricare and other military health care (<i>New</i>)  14 = IHS (<i>New</i>)  15 = Other plan (<i>New</i>)  16 = No insurance/uninsured (<i>New</i>)</p> <p>The allowed values below have been removed:  1 = Private (<i>Removed</i>)  3 = Medicaid (<i>Removed</i>)  4 = Other Public (<i>Removed</i>)  5 = No Insurance (<i>Removed</i>)  6 = Other (<i>Removed</i>)  7 = Unknown (<i>Removed</i>)</p> <p>The allowed values below are not used for the RSR:  8 = Medicare Part A/B (<i>Value not used for RSR</i>)  9 = Medicare Part D (<i>Value not used for RSR</i>)</p>
<b>Schema</b>	<p>Within the following schema section, multiple MedicalInsuranceIDs may be reported. Where multiple MedicalInsuranceIDs are reported, multiple sets of corresponding tags should appear (one for each ID)</p> <pre> &lt;ClientReportMedicalInsurance&gt;   &lt;MedicalInsuranceID&gt;2, 10-16&lt;/MedicalInsuranceID&gt;   ...   &lt;MedicalInsuranceID&gt;2, 10-16&lt;/MedicalInsuranceID&gt; &lt;/ClientReportMedicalInsurance&gt; </pre>

### 3.4.20 *HIVDiagnosisYear (New)*

Field	Description
<b>Reference ID</b>	72
<b>Element Name</b>	HIVDiagnosisYear
<b>Parent Element</b>	ClientReport

Field	Description
<b>Definition</b>	Year of client's HIV diagnosis, if known. To be completed for a new client when the response is not "HIV-negative" or "HIV indeterminate" for HivAidsStatusID. This value must be on or before the last date of the reporting period.
<b>Required</b>	CM, OA  For a new client, if the response for HivAidsStatusID is not "HIV-negative" or "HIV indeterminate" (i.e., HivAidsStatusID ≠ 1 or HivAidsStatusID ≠ 7).
<b>Occurrence</b>	1 per required client
<b>Allowed Values</b>	yyyy  Must be less than or equal to the reporting period year.
<b>Schema</b>	<HivDiagnosisYear>yyyy</HivDiagnosisYear>

### 3.5 Core Medical Service Visits Delivered (Revised)

Field	Description
<b>Reference IDs</b>	16, 18–19, 21–27
<b>Element Name</b>	ClientReportServiceVisits ServiceVisit ( <i>New</i> ) QuarterID ( <i>Removed</i> ) ServiceID Visits
<b>Parent Element</b>	ClientReport
<b>Definition</b>	The number of visits received for each core medical service during the reporting period.
<b>Required</b>	All
<b>Occurrence</b>	0-1 for each core medical service delivered
<b>Allowed Values</b>	QuarterID ( <i>Removed</i> )  Core Medical Services: ServiceIDs: 8 = Outpatient ambulatory health services 10 = Oral health care 11 = Early intervention services (Parts A and B) 13 = Home health care 14 = Home and community-based health services 15 = Hospice services 16 = Mental health services 17 = Medical nutrition therapy 18 = Medical case Management (including treatment adherence) 19 = Substance abuse services-outpatient  Visits: 1–365 (must be an integer)

Field	Description
<b>Schema</b>	<p>Only one ClientReportServiceVisits element may be reported per client record. Multiple ServiceVisit elements may be reported in one ClientReportServiceVisits element. When reporting multiple services, repeat the entire ServiceVisit element. Only one ServiceID and Visits element may appear within a single occurrence of the ServiceVisit element.</p> <pre> &lt;ClientReportServiceVisits&gt;   &lt;ServiceVisit&gt;     &lt;ServiceID&gt;8,10,11,13-19&lt;/ServiceID&gt;     &lt;Visits&gt;1-365&lt;/Visits&gt;   &lt;/ServiceVisit&gt;   ...   &lt;ServiceVisit&gt;     &lt;ServiceID&gt;8,10,11,13-19&lt;/ServiceID&gt;     &lt;Visits&gt;1-365&lt;/Visits&gt;   &lt;/ServiceVisit&gt; &lt;/ClientReportServiceVisits&gt; </pre> <p>Only report services with actual visits. Do not report services without visits.</p>

### 3.6 Core Medical and Support Services Delivered **(Revised)**

Field	Description
<b>Reference IDs</b>	17, 20, 28–45
<b>Element Name</b>	ClientReportServiceDelivered ServiceDelivered ( <i>New</i> ) QuarterID ( <i>Removed</i> ) ServiceID DeliveredID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	The service and service delivered indicator for each core medical or support service received by the client during the reporting period.
<b>Required</b>	All
<b>Occurrence</b>	0-1 for each service delivered

Field	Description
<b>Allowed Values</b>	<p>QuarterID (<i>Removed</i>)</p> <p>Core Medical Services: ServiceID:            9 = Local AIDS Pharmaceutical Assistance (APA, not ADAP)            12 = Health Insurance Program(HIP)</p> <p>Support Services: ServiceID:            20 = Case management (non-medical) services            21 = Child care services            22 = Developmental assessment/early intervention services            23 = Emergency financial assistance            24 = Food bank/home-delivered meals            25 = Health education/risk reduction            26 = Housing services            27 = Legal services            28 = Linguistic services            29 = Transportation services            30 = Outreach services            31 = Permanency planning            32 = Psychosocial support services            33 = Referral for health care/supportive services            34 = Rehabilitation services            35 = Respite care            36 = Substance abuse services-residential            37 = Treatment adherence counseling</p> <p>DeliveredID:            1 = No (<i>Removed</i>)            2 = Yes            3 = Unknown (<i>Removed</i>)</p>
<b>Schema</b>	<p>Only one ClientReportServiceDelivered element may be reported per client record. Multiple ServiceDelivered elements may be reported in one ClientReportServiceDelivered element. When reporting multiple services, repeat the entire ServiceDelivered element. Only one ServiceID and DeliveredID element may appear within a single occurrence of the ServiceDelivered element.</p> <pre> &lt;ClientReportServiceDelivered&gt;   &lt;ServiceDelivered&gt;     &lt;ServiceID&gt;9,12,20-37&lt;/ServiceID&gt;     &lt;DeliveredID&gt;2&lt;/DeliveredID&gt;   &lt;/ServiceDelivered&gt;   ...   &lt;ServiceDelivered&gt;     &lt;ServiceID&gt;9,12,20-37&lt;/ServiceID&gt;     &lt;DeliveredID&gt;2&lt;/DeliveredID&gt;   &lt;/ServiceDelivered&gt; &lt;/ClientReportServiceDelivered&gt; </pre> <p>Only report services that were actually delivered. Do not report services that were not delivered.</p>



## 3.7 Clinical Information

### 3.7.1 *RiskScreeningProvidedID (Revised)*

Field	Description
Reference ID	46
Element Name	RiskScreeningProvidedID
Parent Element	ClientReport
Definition	Value indicating whether the client received risk reduction screening/counseling during this reporting period.
Required	OA
Occurrence	0-1 per required client
Allowed Values	RiskScreeningProvidedID: 1 = No 2 = Yes  The allowed value below has been removed: 3 = Unknown ( <i>Removed</i> )
Schema	<RiskScreeningProvidedID>1-2</RiskScreeningProvidedID>

### 3.7.2 *FirstAmbulatoryCareDate*

Field	Description
Reference ID	47
Element Name	FirstAmbulatoryCareDate
Parent Element	ClientReport
Definition	Date of client's first ambulatory care date at this provider agency.  This value must be on or before the last date of the reporting period.
Required	OA
Occurrence	0-1 per required client
Allowed Values	FirstAmbulatoryCareDate: mm,dd,yyyy
Schema	<FirstAmbulatoryCareDate>mm,dd,yyyy</FirstAmbulatoryCareDate>

### 3.7.3 *ClientReportAmbulatoryService*

Field	Description
Reference ID	48
Element Name	ClientReportAmbulatoryService ServiceDate
Parent Element	ClientReport
Definition	All the dates of the client's outpatient ambulatory care visits in this provider's HIV care setting with a clinical care provider during this reporting period.  The service dates must be within the reporting period.
Required	OA
Occurrence	0-number of days in reporting period per required client
Allowed Values	ServiceDate: mm,dd,yyyy  Must be within the reporting period start and end dates.

Field	Description
Schema	<p>Multiple ServiceDate elements may appear [one for each date] in the ClientReportAmbulatoryService element.</p> <pre> &lt; ClientReportAmbulatoryService&gt;   &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt;   ...   &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt; &lt;/ClientReportAmbulatoryService&gt; </pre>

### 3.7.4 ClientReportCd4Test (Revised)

Field	Description
Reference ID	49
Element Name	<p>ClientReportCd4Test Cd4Test Count ServiceDate</p> <p><b>NOTE:</b> The structure of this data element has changed.</p>
Parent Element	ClientReport
Definition	<p>Values indicating all CD4 counts and their dates for this client during this report period.</p> <p>The service dates must be within the reporting period.</p>
Required	OA
Occurrence	0-number of days in reporting period per required client
Allowed Values	<p>Count: Integer</p> <p>ServiceDate: mm,dd,yyyy</p> <p>Must be within the reporting period start and end dates.</p>
Schema	<p>When reporting multiple CD4 tests, repeat the entire Cd4Test element. Only one Count and ServiceDate element may appear within a single occurrence of the ClientReportCd4Test element.</p> <pre> &lt;ClientReportCd4Test&gt;   &lt;Cd4Test&gt;     &lt;Count&gt;Integer&lt;/Count&gt;     &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt;   &lt;/Cd4Test&gt;   ...   &lt;Cd4Test&gt;     &lt;Count&gt;Integer&lt;/Count&gt;     &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt;   &lt;/Cd4Test&gt; &lt;/ClientReportCd4Test&gt; </pre>

### 3.7.5 ClientReportViralLoadTest (Revised)

Field	Description
Reference ID	50

Field	Description
<b>Element Name</b>	ClientReportViralLoadTest ViralLoadTest Count ServiceDate  <b>NOTE:</b> The structure of this data element has changed.
<b>Parent Element</b>	ClientReport
<b>Definition</b>	All Viral Load counts and their dates for this client during this report period
<b>Required</b>	OA
<b>Occurrence</b>	0-number of days in reporting period
<b>Allowed Values</b>	Count: Integer  Report undetectable values as the lower bound of the test limit. If the lower bound is not available, report 0. Convert values, such as, 0.12345 x 1000 to 1234.  ServiceDate: mm,dd,yyyy  Must be within the reporting period start and end dates.
<b>Schema</b>	When reporting multiple viral load tests, repeat the entire ViralLoadTest element. Only one Count and ServiceDate element may appear within a single occurrence of the ClientReportViralLoadTest element.  <pre> &lt;ClientReportViralLoadTest&gt;   &lt;ViralLoadTest&gt;     &lt;Count&gt;Integer&lt;/Count&gt;     &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt;   &lt;/ViralLoadTest&gt;   ...   &lt;ViralLoadTest&gt;     &lt;Count&gt;Integer&lt;/Count&gt;     &lt;ServiceDate&gt;mm,dd,yyyy&lt;/ServiceDate&gt;   &lt;/ViralLoadTest&gt; &lt;/ClientReportViralLoadTest&gt; </pre>

### 3.7.6 PrescribedPcpProphylaxisID (Revised)

Field	Description
<b>Reference ID</b>	51
<b>Element Name</b>	PrescribedPcpProphylaxisID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Value indicating whether the client was prescribed PCP Prophylaxis anytime during this reporting period.
<b>Required</b>	OA
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated 4 = No, client refused  The allowed value below has been removed: 5 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<PrescribedPcpProphylaxisID>1-4 </ PrescribedPcpProphylaxisID>

### 3.7.7 PrescribedArtID (Revised)

Field	Description
Reference ID	52
Element Name	PrescribedArtID
	<b>NOTE:</b> "PrescribedHaartID" has been renamed "PrescribedArtID".
Parent Element	ClientReport
Definition	Value indicating whether the client prescribed ART at any time during this reporting period.
Required	OA
Occurrence	0-1 per required client
Allowed Values	1 = Yes 3 = No, not ready (as determined by clinician) 4 = No, client refused 5 = No, intolerance, side-effect, toxicity 6 = No, ART payment assistance unavailable 7 = No, other reason  The allowed values below have been removed: 2 = No, not medically indicated ( <i>Removed</i> ) 8 = Unknown ( <i>Removed</i> )
Schema	<PrescribedArtID> 1,3-7</ PrescribedArtID>

### 3.7.8 ScreenedTBID (Removed)

Field	Description
Reference ID	53
Element Name	ScreenedTBID
Comments	This data element has been removed and should not be included in the client-level data XML file.

### 3.7.9 ScreenedTBSinceHivDiagnosisID (Revised)

Field	Description
Reference ID	54
Element Name	ScreenedTBSinceHivDiagnosisID
Parent Element	ClientReport
Definition	Value indicating whether the client has been screened for TB since his/her HIV diagnosis.
Required	OA
	<b>NOTE:</b> This data element is now required for all clients for whom Clinical Information is reported.
Occurrence	0-1 per required client
Allowed Values	ScreenedTBSinceHivDiagnosisID: 1 = No 2 = Yes 3 = Not medically indicated 4 = Unknown
Schema	<ScreenedTBSinceHivDiagnosisID>1–4</ScreenedTBSinceHivDiagnosisID>

### 3.7.10 **ScreenedSyphilisID** (Revised)

Field	Description
Reference ID	55
Element Name	ScreenedSyphilisID
Parent Element	ClientReport
Definition	Value indicating whether the client was screened for syphilis during this reporting period (exclude all clients under the age of 18 who are not sexually active)
Required	OA if client is 18 years of age, or older
Occurrence	0-1 per required client
Allowed Values	1 = No 2 = Yes 3 = Not medically indicated  The allowed value below has been removed: 4 = Unknown (Removed)
Schema	<ScreenedSyphilisID>1-3</ScreenedSyphilisID>

### 3.7.11 **ScreenedHepatitisBID** (Removed)

Field	Description
Reference ID	56
Element Name	ScreenedHepatitisBID
Comments	This data element has been removed and should not be included in the client-level data XML file.

### 3.7.12 **ScreenedHepatitisBSinceHivDiagnosisID** (Revised)

Field	Description
Reference ID	57
Element Name	ScreenedHepatitisBSinceHivDiagnosisID
Parent Element	ClientReport
Definition	Value indicating whether the client has been screened for Hepatitis B since his/her HIV diagnosis.
Required	OA  <b>NOTE:</b> This data element is now required for all clients for whom Clinical Information is reported.
Occurrence	0-1 per required client
Allowed Values	1 = No 2 = Yes 3 = Not medically indicated 4 = Unknown
Schema	ScreenedHepatitisBSinceHivDiagnosisID> 1-4 </ScreenedHepatitisBSinceHivDiagnosisID>

### 3.7.13 **VaccinatedHepatitisBID** (Revised)

Field	Description
Reference ID	58
Element Name	VaccinatedHepatitisBID
Parent Element	ClientReport

Field	Description
<b>Definition</b>	Value indicating whether the client has completed the vaccine series for Hepatitis B.
<b>Required</b>	OA
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated  The allowed value below has been removed: 4 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<VaccinatedHepatitisBID>1-3</VaccinatedHepatitisBID>

### 3.7.14 **ScreenedHepatitisCID** (*Removed*)

Field	Description
<b>Reference ID</b>	59
<b>Element Name</b>	ScreenedHepatitisCID
<b>Comments</b>	This data element has been removed and should not be included in the client-level data XML file.

### 3.7.15 **ScreenedHepatitisCSinceHivDiagnosisID** (*Revised*)

Field	Description
<b>Reference ID</b>	60
<b>Element Name</b>	ScreenedHepatitisCSinceHivDiagnosisID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Value indicating whether the client has been screened for Hepatitis C since his/her HIV diagnosis.
<b>Required</b>	OA  <b>NOTE:</b> This data element is now required for all clients for whom Clinical Information is reported.
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated 4 = Unknown
<b>Schema</b>	<ScreenedHepatitisCSinceHivDiagnosisID> 1-4 </ScreenedHepatitisCSinceHivDiagnosisID>

### 3.7.16 **ScreenedSubstanceAbuseID** (*Revised*)

Field	Description
<b>Reference ID</b>	61
<b>Element Name</b>	ScreenedSubstanceAbuseID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Value indicating whether the client was screened for substance use (alcohol and drugs) during this reporting period.
<b>Required</b>	OA
<b>Occurrence</b>	1 per required client

Field	Description
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated  The allowed value below has been removed: 4 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<ScreenedSubstanceAbuseID>1-3</ScreenedSubstanceAbuseID>

### 3.7.17 **ScreenedMentalHealthID** (*Revised*)

Field	Description
<b>Reference ID</b>	62
<b>Element Name</b>	ScreenedMentalHealthID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Value indicating whether the client was screened for mental health during this reporting period.
<b>Required</b>	OA
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated  The allowed value below has been removed: 4 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<ScreenedMentalHealthID>1-3 </ScreenedMentalHealthID>

### 3.7.18 **ReceivedCervicalPapSmearID** (*Revised*)

Field	Description
<b>Reference ID</b>	63
<b>Element Name</b>	ReceivedCervicalPapSmearID
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Value indicating whether the client received a Pap smear during the reporting period.
<b>Required</b>	OA  This should be completed for HIV-positive women only.
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not medically indicated 4 = Not applicable  The allowed value below has been removed: 5 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<ReceivedCervicalPapSmearID>1-4</ReceivedCervicalPapSmearID>

### 3.7.19 **PregnantID** (*Revised*)

Field	Description
<b>Reference ID</b>	64
<b>Element Name</b>	PregnantID
<b>Parent Element</b>	ClientReport

Field	Description
<b>Definition</b>	Value indicating whether the client was pregnant during this reporting period.
<b>Required</b>	OA  This should be completed for HIV-positive women only.
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	1 = No 2 = Yes 3 = Not applicable  The allowed value below has been removed: 4 = Unknown ( <i>Removed</i> )
<b>Schema</b>	<PregnantID>1-3</PregnantID>

### 3.7.20 *PrenatalCareID (Removed)*

Field	Description
<b>Reference ID</b>	65
<b>Element Name</b>	PrenatalCareID
<b>Comments</b>	This data element has been removed and should not be included in the client-level data XML file.

### 3.7.21 *PrescribedArvMedicationID (Removed)*

Field	Description
<b>Reference ID</b>	66
<b>Element Name</b>	PrescribedArvMedicationID
<b>Comments</b>	This data element has been removed and should not be included in the client-level data XML file.

## 3.8 HIV Counseling and Testing Elements

### 3.8.1 *HivPosTestDate (New)*

Field	Description
<b>Reference ID</b>	73
<b>Element Name</b>	HivPosTestDate
<b>Parent Element</b>	ClientReport
<b>Definition</b>	Date of client's confidential confirmatory HIV test with a positive result within the reporting period.
<b>Required</b>	All newly diagnosed OAMC clients with a confidential positive HIV confirmatory test during the reporting period.
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	mm,dd,yyyy  Must be within the reporting period.
<b>Schema</b>	<HivPosTestDate>mm,dd,yyyy</HivPosTestDate>

### 3.8.2 *OamcLinkDate (New)*

Field	Description
<b>Reference ID</b>	74
<b>Element Name</b>	OamcLinkDate
<b>Parent Element</b>	ClientReport



Field	Description
<b>Definition</b>	Date of client's first OAMC visit after positive HIV test.  Date must be the same day or after the date of client's confidential confirmatory HIV test with a positive result.
<b>Required</b>	All newly diagnosed OAMC clients with a confidential positive HIV confirmatory test during the reporting period.
<b>Occurrence</b>	0-1 per required client
<b>Allowed Values</b>	mm,dd,yyyy  Must be within the reporting period.
<b>Schema</b>	<OamcLinkDate>mm,dd,yyyy</OamcLinkDate>

## 4 RSR Client-level Data XML File Format

The RSR client-level data XML file structure and content is defined through a set of XML Schema Definition (XSD) files. The XSD files are used to validate the RSR client-level data XML files before they can be loaded into the RSR Web application. Once loaded, further checks are performed by the RSR Web application.

### 4.1 RSR Web Application Validation Checks

The following validation checks must be satisfied before an RSR client-level data XML file will be accepted by the RSR Web application:

- The XML file must have the .xml extension.
- The XML file must conform to the XML Schema Definition files.
- One and only one set of records per client is allowed in a single client-level data XML file.
- An encrypted unique client identifier (i.e., ClientUci) may not be repeated within the same XML file. A client is uniquely identified by their encrypted unique client Identifier (eUCI). This value is represented in the RSR client-level data XML file by the ClientUci data element within the RsrClientReport complex element. The ClientUci value is an upper-cased, 40 character, hexadecimal value (0-9, A-F) followed by a single suffix from A through Z used to further identify clients that may share the same base, 40 character encrypted UCI.
- The XML data elements must appear in the specified order. See Section 4.2: Sample XML File Format for an example of the sequencing required.
- The XML simple data elements must conform to the definitions appearing in this document. Required fields must be reported and values must be valid and match the documented format, if defined.

Empty or "NULL" data element tags are not permitted in the XML file. For example, data elements of the form <tag></tag> or <tag /> are not allowed. **NOTE:** If data will not be provided for an element for a particular client, then remove that element entirely from the client's record (i.e., remove the data element's start tag, value, and end tag).

## 4.2 Sample Client-Level Data XML Format

This example shows a sample client-level data XML file with the required sequence of data elements that are included in the file. Please note that this data are solely used as an example and represent the structure, sequence, values, and format of the data elements.

```
<?xml version="1.0" encoding="UTF-8"?>
<RSR:ROOT xsi:schemaLocation="urn:rsrNamespaces
  https://performance.hrsa.gov/hab/rsrExternal/App/XMLSchema/RsrClientSchema.xsd"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:RSR="urn:rsrNamespaces">
  <XmlVersion>
    <SchemaVersion>4 0 0</SchemaVersion>
    <Originator>Application Name</Originator>
    <VersionNumber>Application Version Number</VersionNumber>
    <TechnicalContactName>Jonathan Doe</TechnicalContactName>
    <TechnicalContactEmail>sample@company.ext</TechnicalContactEmail>
    <TechnicalContactPhone>555,555,1234</TechnicalContactPhone>
    <ReportYear>2014</ReportYear>
  </XmlVersion>
  <ClientReport>
    <ProviderID>100</ProviderID>
    <RegistrationCode>10001</RegistrationCode>
    <ClientUci>0123456789ABCDEF0123456789ABCDEF01234567U</ClientUci>
    <EnrollmentStatusID>5</EnrollmentStatusID>
    <BirthYear>1985</BirthYear>
    <EthnicityID>2</EthnicityID>
    <ClientReportRace>
      <RaceID>6</RaceID>
    </ClientReportRace>
    <GenderID>3</GenderID>
    <TransgenderID>1</TransgenderID>
    <PovertyLevelID>12</PovertyLevelID>
    <HousingStatusID>2</HousingStatusID>
    <HivAidsStatusID>1</HivAidsStatusID>
    <ClientReportHivRiskFactor>
      <HivRiskFactorID>8</HivRiskFactorID>
    </ClientReportHivRiskFactor>
    <ClientReportMedicalInsurance>
      <MedicalInsuranceID>6</MedicalInsuranceID>
    </ClientReportMedicalInsurance>
    <ClientReportServiceVisits>
      <ServiceVisit>
        <ServiceID>8</ServiceID>
        <Visits>5</Visits>
      </ServiceVisit>
      <ServiceVisit>
        <ServiceID>14</ServiceID>
        <Visits>5</Visits>
      </ServiceVisit>
    </ClientReportServiceVisits>
    <ClientReportServiceDelivered>
      <ServiceDelivered>
        <ServiceID>20</ServiceID>
        <DeliveredID>2</DeliveredID>
      </ServiceDelivered>
    </ClientReportServiceDelivered>
  </ClientReport>
</RSR:ROOT>
```

```

</ServiceDelivered>
<ServiceDelivered>
  <ServiceID>33</ServiceID>
  <DeliveredID>2</DeliveredID>
</ServiceDelivered>
</ClientReportServiceDelivered>
<RiskScreeningProvidedID>2</RiskScreeningProvidedID>
<FirstAmbulatoryCareDate>1,1,2011</FirstAmbulatoryCareDate>
<ClientReportAmbulatoryService>
  <ServiceDate>1,1,2013</ServiceDate>
  <ServiceDate>4,1,2013</ServiceDate>
  <ServiceDate>7,1,2013</ServiceDate>
  <ServiceDate>10,1,2013</ServiceDate>
</ClientReportAmbulatoryService>
<ClientReportCd4Test>
  <Cd4Test>
    <Count>830</Count>
    <ServiceDate>1,1,2013</ServiceDate>
  </Cd4Test>
  <Cd4Test>
    <Count>875</Count>
    <ServiceDate>8,1,2013</ServiceDate>
  </Cd4Test>
</ClientReportCd4Test>
<ClientReportViralLoadTest>
  <ViralLoadTest>
    <Count>210</Count>
    <ServiceDate>1,1,2013</ServiceDate>
  </ViralLoadTest>
  <ViralLoadTest>
    <Count>175</Count>
    <ServiceDate>8,1,2013</ServiceDate>
  </ViralLoadTest>
</ClientReportViralLoadTest>
<PrescribedPcpProphylaxisID>1</PrescribedPcpProphylaxisID>
<PrescribedArtID>6</PrescribedArtID>
<ScreenedTBSinceHivDiagnosisID>2</ScreenedTBSinceHivDiagnosisID>
<ScreenedSyphilisID>3</ScreenedSyphilisID>
<ScreenedHepatitisBSinceHivDiagnosisID>3</ScreenedHepatitisBSinceHivDiagnosisID>
<VaccinatedHepatitisBID>1</VaccinatedHepatitisBID>
<ScreenedHepatitisCSinceHivDiagnosisID>1</ScreenedHepatitisCSinceHivDiagnosisID>
<ScreenedSubstanceAbuseID>1</ScreenedSubstanceAbuseID>
<ScreenedMentalHealthID>2</ScreenedMentalHealthID>
<ReceivedCervicalPapSmearID>1</ReceivedCervicalPapSmearID>
<PregnantID>1</PregnantID>
<ClientReportHispanicSubgroup>
  <SubgroupID>2</SubgroupID>
</ClientReportHispanicSubgroup>
<ClientReportAsianSubgroup>
  <SubgroupID>3</SubgroupID>
</ClientReportAsianSubgroup>
<ClientReportNhpiSubgroup>
  <SubgroupID>1</SubgroupID>
</ClientReportNhpiSubgroup>
<SexAtBirthID>1</SexAtBirthID>
<HivDiagnosisYear>2003</HivDiagnosisYear>

```

```
<HivPosTestDate>12,1,2011</HivPosTestDate>  
<OamcLinkDate>12,6,2011</OamcLinkDate>  
</ClientReport>  
</RSR:ROOT>
```

## Appendix A: List of Acronyms

ADAP	AIDS Drug Assistance Program
AIDS	Acquired ImmunoDeficiency Syndrome
APA	AIDS Pharmaceutical Assistance
ART	AntiRetroviral Therapy
C&T	(HIV) Counseling and Testing
CHIP	Children's Health Insurance Program
CM	Case Management Services (Medical and Non-medical)
eUCI	Encrypted Unique Client Identifier
HAB	HIV/AIDS Bureau
HIP	Health Insurance Program
HIV	Human Immunodeficiency Virus
HRSA	Health Resources and Services Administration
IHS	Indian Health Service
OA	Outpatient/ambulatory Medical Care Services
RDR	Ryan White HIV/AIDS Program Data Report
RSR	Ryan White HIV/AIDS Program Services Report
RWHAP	Ryan White HIV/AIDS Program
UCI	Unique Client Identifier
XML	eXtensible Markup Language
XMLNS	XML Namespace
XSD	XML Schema Definition
XSI	XML Schema Instance
VA	Veterans Affairs

## **Appendix B: Resources**

### **RSR XML Schema Definitions**

The RSR XML schema definitions and sample XML files can be downloaded from the [Ryan White Services Report Download Package](#) page on the TARGET Center website.

### **RSR Instruction Manual**

The RSR Instruction Manual contains detailed information needed for completing the RSR. This document may be cross-referenced with the [RSR Instructions document](#).

### **TRAX (XML generator)**

The [Tool for RSR and ADR XML Generation \(TRAX\)](#) is a HAB tool that can be used to generate the RSR client-level data XML files. This tool is available on the TARGET Center website.

### **HRSA/HAB RSR Website**

The [HRSA/HAB RSR website](#) contains a comprehensive collection of information related to RSR.

### **TARGET Center Website**

The [TARGET Center website](#) contains a vast array of technical assistance resources including the TRAX application, webcasts, training materials, and reference documents, such as the RSR Instruction Manual.